Directional Control Valves ND 4

manually operated, max. operating pressure 500 bar



General characteristics

Type Poppet valve
Type of connection Subplate mounted

(see accessories)

Port size G 1/4 Weight 0.4 kg

Hydraulic characteristics

Adm. operating press. 0-500 bar Adm. flow rate 8 l/min

Direction of flow only in direction of

arrow as in symbol


Hydraulic oil HLP 22


Operating specification


Manually operated

Angle of rotation 90°
Operating torque 0.63 Nm

Double-acting function see data sheet C 2.345.








Seal (sp	Part-no.	
at A:	O-ring Ø 5x1.5	3000-340
at P:	O-ring Ø 8x1.5	3000-343
at R:	O-ring Ø 8x1.5	3000-343


Description	Symbol	Part-no.
2/2 directional control valve without check valve	₩ ₽	2321-302
3/2 directional control valve without check valve		2321-201
3/2 directional control valve with built-in check valve		2321-300

Accessories

Mounting plate

 Δ p-Q characteristic curve for kinematic viscosity of 53x10-6 m²/s (HLP 22 at 20 °C)





3534-039

网址: www.fdzc.net 联系人: 程家雄 手机: 13601809714

联系电话: 021-51872743 E-mail:chengff@sh163.net